

# LUBRA-GLIDE "CE" CO-POLYMER BEADS®

THE ONLY BEAD MADE EXCLUSIVELY FOR THE PETROLEUM INDUSTRY.

## Advantages

- ◆ Reduces torque and drag
- ◆ Reduces casing wear
- ◆ Is non-abrasive
- ◆ Is recoverable using Sun's patented process
- ◆ Is thermally stable up to 500°F
- ◆ Is compatible with both oil and water base mud
- ◆ Is environmentally safe
- ◆ Resistance to deformation is greater than 25,000 psi hydrostatic, thermally stable down hole to 500°F in a drilling environment

## Physical Properties

- ◆ Form: Spherical Solid Bead
- ◆ Color: Clear
- ◆ Specific gravity: 1.06

## Application


- ◆ Concentrations of 2 – 8 ppb (5.71 – 22.87 Kg/m<sup>3</sup>) will be sufficient to control torque and drag
- ◆ Concentrations of 8 – 12 ppb (22.87 – 34.31 Kg/m<sup>3</sup>) will be sufficient for spotting in wire-line operations and running casing
- ◆ LUBRA-GLIDE "CE" CO-POLYMER BEADS® (coarse and fine) should mix through the mud-mixing hopper

## Packaging

- ◆ LUBRA-GLIDE "CE" CO-POLYMER BEADS® is available in 50 lbs (22.6 Kg) sacks, 48 or 50 sacks per pallet

## Typical Uses for LUBRA-GLIDE "CE" CO-POLYMER BEADS®

- ◆ Spot in hole prior to running casing or liners
- ◆ Spot in hole prior to logging operations
- ◆ Allows more true weight to bit
- ◆ Spot in key seats to reduce torque, drag, and sticking problems
- ◆ Apply LUBRA-GLIDE "CE" CO-POLYMER BEADS® fine beads for torque and drag in coil tubing operations or with work strings
- ◆ Lubricant for OBM or SBM
- ◆ Aids in prevention of differential sticking when using OBM or SBM
- ◆ Aids in directional changes or sliding



*Sun ... The HOLE Solution Company*

**1-800-962-6490**

[www.sundrilling.com](http://www.sundrilling.com)

Houston, Texas 713.690.3939  
Pinedale, Wyoming 307.231.1008  
Belle Chasse, Louisiana 504.393.2778  
Oklahoma City, Oklahoma

Western Hemisphere 888.311.6604  
Eastern Hemisphere +44.1603.667020  
Calgary, Alberta Canada 403.319.0677  
Denver, Colorado  
082305